

Electric Manual Platform Stacker



PS200-85/200-120
 /400-85/400-120/
 400-150/400-170



EPS200-85/200-120
 /400-85/400-120/
 400-150/400-170



PS200-85FF/200-120FF
 /400-85FF/400-120FF/
 400-150FF/400-170FF



PS200-85AF/200-120AF
 /400-85AF/400-120AF/
 400-150AF/400-170AF



EPS200-85FF/200-120FF
 /400-85FF/400-120FF/
 400-150FF/400-170FF



EPS200-85AF/200-120AF
 /400-85AF/400-120AF/
 400-150AF/400-170AF



EPS400U-121
 /EPS400U-127
 /EPS400U-121AF



OP200

Specification Data

Specification	Liftstar Model		(E)PS200-85	(E)PS200-120	(E)PS400-85	(E)PS400-120	(E)PS400-150	(E)PS400-170
	Capacity	kg	200	200	400	400	400	400
	Platform Height Max.	H (mm)	850	1200	850	1200	1500	1700
	Platform Height Min.	H1 (mm)	200	200	200	200	200	200
	Platform Length	L1 (mm)	600	600	650	650	650	650
	Platform Width	W (mm)	500	500	550	550	550	550
	Total Length(PS/EPS)	L (mm)	940/(990)	940/(990)	1040/(1070)	1040/(1070)	1040/(1070)	1040/(1070)
	Total Width	B (mm)	560	560	590	590	590	590
	Total Height	H2 (mm)	960	1310	970	1310	1610	1810
	Steering Rollers-diameter	D (mm)	125	125	150	150	150	150
	Frame Rollers-diameter	d (mm)	125	125	150	150	150	150
	Power motor (EPS)	KW	0.8	0.8	0.8	0.8	0.8	0.8
	Battery(EPS)	V/Ah	12/60	12/60	12/70	12/70	12/70	12/70
	Pump Strokes to Max. Height	Times	19	26	35	50	63	71
Net Weight(PS/EPS)	kg	53/(88)	58/(93)	72/(107)	78/(113)	83/(118)	93/(128)	

Specification	Liftstar Model		(E)PS200-85FF/AF	(E)PS200-120FF/AF	(E)PS400-85FF/AF	(E)PS400-120FF/AF	(E)PS400-150FF/AF	(E)PS400-170FF/AF
	Capacity	(kg)	200		400			
	Max.Fork Height	(mm)	850	1200	850	1200	1500	1700
	Min.Fork Height	(mm)	85		85			
	Fork Length	(mm)	600		650			
	Fixed Fork Width	(E)PS-FF (mm)	500		550			
	Adjustable Fork Width	(E)PS-AF (mm)	215-500		235-500			
	Load Roller	(mm)	Φ75		Φ75			
	Steering Wheel	(mm)	Φ125		Φ125			
	Pump strokes to Max.Height	times	19	26	35	50	63	71
	Power motor	EPS(KW)	0.8		0.8			
	Battery	V/Ah	12/60					
	Overall Height	(mm)	1080	1435	1060	1410	1710	1910
	Overall Width	(mm)	560		590			
Overall Length	PS(mm)	1000	960	1040	1040	1040	1100	
	EPS(mm)	1020	1020	1110				
Net Weight	PS-FF (kg)	55	62	70	76	82	92	
	PS-AF (kg)	58	65	75	81	85	95	
	EPS-FF (kg)	90	97	105	116	122	132	
	EPS-AF (kg)	93	100	110	121	127	137	

Specification	Liftstar Model		EPS400U-121	EPS400U-127	EPS400U-121AF
	Type		Platform	Platform	Adjustable Fork
	Capacity	kg	400	400	400
	Platform(Fork) Height Max.	mm	1210	1270	1210
	Platform(Fork) Height Min.	mm	90	150	90
	Platform(Fork) Length	mm	670	670	700
	Single Fork Width	mm	-	-	-
	Platform(Fork) Width	mm	590	590	190-572
	Total Width	mm	620	620	620
	Total Length	mm	1190	1190	1270
	Total Height	mm	1610	1635	1610
	Steering Rollers-diameter	mm	Φ75	Φ75	Φ75
	Frame Rollers-diameter	mm	Φ125	Φ125	Φ125
	Power Pack Motor	KW	0.8	0.8	0.8
Battery	V/Ah	12/70	12/70	12/70	
Net Weight	kg	116	118	C	

Specification	Model		OP200
	Capacity	kg	200(including operator)
	Platform(Fork) Height Max.	mm	1500
	Platform(Fork) Height Min.	mm	670
	Platform(Fork) Length	mm	600
	Platform(Fork) Width	mm	550
	Power Pack Motor	KW	DC 0.8Kw
	Battery	V/Ah	12/60
Net Weight	kg	151	
Over all size	mm	1210×630×1040mm	

- ⊙ (E)PS: (Electric) Manual Platform Stacker
200 :Cap.
85 :Lifting height
- ⊙ (E)PS: (Electric) Manual Platform Stacker
200 :Cap.
85 :Lifting height
FF: Fixed Fork type
AF: Adjustable Fork Type
- ⊙ (E)PS: (Electric) Manual Platform Stacker
400 :Cap.
U : Upgrades version
127:Lifting height
FF: Fixed Fork type
AF: Adjustable Fork Type
- ⊙ OP: Electric Order Picker