

Overhead Block Clamp



Let the
forklift
become a
universal
forklift



Functions & Applications

Securely and efficiently handle and stack nearly any type of masonry products and cubic goods including aerated blocks, prefabricated cement, masonry products and graphite without pallet.

Features

- 0°~90° rotation
- Telescopic arm is convenient for handling blocks in a certain distance.
- Active arm adjusts the bricks to be flat in small range.
- Damping cylinder can ensure stable operation and reduce shaking during loading block

Overhead Block Clamp



Capacity@ Load Center	Catalog Order No.	Mounting Class	Opening Range	Extend Range	Rotating Angle	Clamp Length	Clamp Height	Clamp Thickness	Frame Height	Frame Width	Weight	Effective Thickness
(kg@mm)			E (mm)	(mm)	(°)	L (mm)	H (mm)	T (mm)	A (mm)	B (mm)	ET (mm)	HCG (mm)
1500	ZKJ15D-C001	III	800-1200	2210-2810	100°	1020	1020	1020	2130	1550	1180	575
1500	ZKJ15D-D001	IV	800-1200	2210-2810	100°	1020	1400	1020	2630	1560	1900	960

Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.

Three sets additional oil circuit required on forklift.

Mounted on 5T forklift or more than 5T.

Please contact the sales from Fujian Longji.