

SPECIFICATIONS



Spec./Model	RT-4000	RT-5000	RT-5500	RT-6500
Lift Capacity @ 24 in. load center	4000 Lbs.	5000 Lbs.	5500 Lbs.	6500 Lbs.
Lift Height (standard)	8 Ft.	10 Ft.	12 Ft.	12 Ft.
Lift Height (optional)	10 Ft.	12 Ft.	10 Ft.	10 Ft.
Overall Height	98.5 In.	104.5 In.	104.5 In.	104.5 In.
Minimum Mounted Overhang	64 In.	75 In.	75 In.	75 In.
Width	100 In.	100 In.	100 In.	100 In.
Weight (Ready To Operate)	3900 Lbs.	5100 Lbs.	5800 Lbs.	6250 Lbs.
Mast Tilt	8°	8°	8°	8°
Side Shift	5 In. (optional)	5 In.	5 In.	5 In.
Frame Opening	60 In.	60 In.	60 In.	60 In.
Fork Travel	30 In.	30 In.	30 In.	30 In.
Drive Tires	(2) 31x15.5x15	(3) 31x15.5x15	(3) 31x15.5x15	(3) 31x15.5x15
Transmission	Hydrostatic drive	Hydrostatic drive	Hydrostatic drive	Hydrostatic drive
Engine	37HP Water Cooled Diesel	60HP Water Cooled Diesel	60HP Water Cooled Diesel	60HP Water Cooled Diesel
Max Travel Speed	9 Mph.	8 Mph.	8 Mph.	8 Mph.
Nav-Reach (optional)	Yes	Yes	Yes	Yes
Automotive Control (optional)	No	Yes	Yes	Yes
Jumbo Caster (optional)	Yes	No	No	No

*Specifications are based on standard model machines. The above specifications are not binding. Chrisman Manufacturing reserves the right to make changes and/or improvements without prior notice