

Electric Scissor Lift

120 Series



Electric Scissor Lift

120 Series



- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- Higher driver comfort and security

Model	AS0812	AS1012	AS1212
Lift Capacity	450 kg	320 kg	320 kg
Extension Lift Capacity	113 kg	113 kg	113 kg
Platform Occupants	2	2	2
Working Height (A + 2.00 m)	10.00 m	12.00 m	14.00 m
Platform Height (A)	8.00 m	10.00 m	12.00 m
Length (B)	2.47 m	2.47 m	2.47 m
Width (C)	1.18 m	1.18 m	1.18 m
Height (D)	2.28 m	2.40 m	2.56 m
Height - rails folded	1.68 m	1.80 m	1.96 m
Platform Dimension (LxB)	2.26 x 1.15 m	2.26 x 1.15 m	2.26 x 1.15 m
Length - platform extension	0.90 m	0.90 m	0.90 m
Ground Clearance - stowed/raised	0.10/0.02 m	0.10/0.02 m	0.10/0.02 m
Wheelbase	1.85 m	1.85 m	1.85 m
Turning Radius - outside	2.30 m	2.30 m	2.30 m
Max. Gradeability	25 %	25 %	25 %
Max. Slope	1,5/3,0 °	2,0/3,0 °	1,5/3,0 °
Up/Down Speed	35/40 sec	62/74 sec	65/90 sec
Driving Speed	0,8 - 3,5 km/h	0,8 - 3,5 km/h	0,8 - 3,1 km/h
Non-marking Tires	380 x 130 mm	380 x 130 mm	380 x 130 mm
Driving Motor	hydraulic	hydraulic	hydraulic
Lifting Motor	24V/3,3kW	24V/3,3kW	24V/3,3kW
Battery	4x6V/240Ah	4x6V/240Ah	24V/300Ah
Charger	24V/30A	24V/30A	24V/30A
Machine Weight	2.691 kg	3.000 kg	3.300 kg

